

# FIRELOCK AUTOMATIC SPRINKLERS

Scan to view the interactive chart



STANDARD  
COVERAGE

EXTENDED  
COVERAGE

RESIDENTIAL

STORAGE

DRY

SPECIFIC  
APPLICATION

# FIRELOCK AUTOMATIC SPRINKLERS

Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.



EXTENDED  
COVERAGE

RESIDENTIAL

STORAGE

DRY

SPECIFIC  
APPLICATION

## QUICK RESPONSE

PUB.	SERIES	DEFLECTOR	K-FACTOR Imp.	SIN NUMBER	CONNECTION TYPE NPT in.   IGS Grooved	TEMPERATURE RATING F	APPROVALS	FINISHES AND CORROSIVE COATINGS	MAX. PRESSURE PSI	ESCUTCHEONS/ COVERPLATES NPT in. x ADJ in.	WRENCHES
41.01	FL-QR	Upright	2.8	V2815	½	135, 155, 175, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	NA	V56 Open End
	FL-QR	Upright	4.2	V4215	½	135, 155, 175, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	NA	V56 Open End
	FL-QR	Upright	5.6	V2704	½   IGS Grooved	135, 155, 175, 200, 286	cULus, FM, LPCB, VdS, CCCf, CE	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	250	NA	V27 Open End, 3/16 Hex-Bit
	FL-QR	Upright	8.0	V3402	¾   IGS Grooved	135, 155, 175, 200, 286	cULus, FM, LPCB, VdS, CCCf, CE	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	NA	V34 Open End, 3/16 Hex-Bit
	FL-QR	Pendent and Recessed Pendent	2.8	V2801	½	135, 155, 175, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	½ x ½, ½ x ¾	V56-2 Recessed, V56 Open End
	FL-QR	Pendent and Recessed Pendent	4.2	V4201	½	135, 155, 175, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	½ x ½, ½ x ¾	V56-2 Recessed, V56 Open End
	FL-QR	Pendent and Recessed Pendent	5.6	V2708	½   IGS Grooved	135, 155, 175, 200, 286	cULus, FM, CCCf	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	250	½ x ½, ½ x ¾	V27-2 Recessed, V27 Open End, 3/16 Hex-Bit
	FL-QR	Pendent and Recessed Pendent	8.0	V3406	¾   IGS Grooved	135, 155, 175, 200	cULus, FM, CCCf	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	¾ x ½, ¾ x ¾	V34-2 Recessed, V34 Open End, 3/16 Hex-Bit
41.02	FL-QR/SW	Horizontal Sidewall and Recessed Horizontal Sidewall	2.8	V2826	½	135, 155, 175, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	½ x ½, ½ x ¾	V56-2 Recessed, V56 Open End
	FL-QR/SW	Horizontal Sidewall and Recessed Horizontal Sidewall	4.2	V4226	½	135, 155, 175, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	½ x ½, ½ x ¾	V56-2 Recessed, V56 Open End
	FL-QR/SW	Horizontal Sidewall and Recessed Horizontal Sidewall	5.6	V2710	½   IGS Grooved	135, 155, 175, 200, 286	cULus, FM, LPCB, CCCf, CE	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	250	½ x ½, ½ x ¾	V27-2 Recessed, V27 Open End, 3/16 Hex-Bit
	FL-QR/SW	Horizontal Sidewall and Recessed Horizontal Sidewall	8.0	V3410	¾   IGS Grooved	135, 155, 175, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	¾ x ½, ¾ x ¾	V34-2 Recessed, V34 Open End, 3/16 Hex-Bit
41.03	FL-QR/C	Concealed Pendent	5.6	V5606	½	135, 155, 175, 200	cULus, FM	Plain Brass, Chrome, White, Bright White, Black, Custom	175	1	1" ADJ Concealed
	FL-QR/C	Concealed Pendent	5.6	V3802	½	135, 155, 175, 200	cULus, FM, LPCB, CCCf, CE	Plain Brass, Chrome, White, Bright White, Black, Custom	175	½	V38 Concealed
	FL-QR/C	Concealed Pendent	5.6	V3808	½	135, 155, 175, 200	cULus	Plain Brass, Chrome, White, Bright White, Black, Custom	300	½	V38 Concealed
41.04	FL-QR/CNV	Conventional	5.6	V2726	½	135, 155, 175, 200, 286	cULus, LPCB, VdS, CE	Plain Brass, Chrome, White, Bright White, VC250	175	NA	V27 Open End
	FL-QR/CNV	Conventional	5.6	V2754	½	135, 155, 175, 200, 286, 360	cULus	Plain Brass, VC250	300	NA	V27 Open End
	FL-QR/CNV	Conventional	8.0	V8125	¾	135, 155, 175, 200, 286	cULus, FM, LPCB, CE	Plain Brass, Chrome, White, Bright White, Black	175	NA	V11 Open End
41.05	FL-QR/EUR	European Pendent	5.6	V2728	½	135, 155, 175, 200, 286	cULus, LPCB, VdS, CE	Plain Brass, Chrome, White, Bright White, VC250	175	NA	V27 Recessed, V27 Open End
	FL-QR/EUR	European Pendent	8.0	V3424	¾	135, 155, 175, 200, 286	LPCB, VdS, CE	Plain Brass, Chrome, White, Bright White, VC250, Custom	175	NA	V34 Recessed, V34 Open End

NOTES: VC250: A Victaulic® proprietary coating that is UL listed and FM approved for corrosive environments. Clean Room Gasket Cover Plates available for all Concealed Pendent deflector sprinklers. Reference the Victaulic® price list or individual publications for more information.



# FIRELOCK AUTOMATIC SPRINKLERS

Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.



EXTENDED  
COVERAGE

RESIDENTIAL

STORAGE

DRY

SPECIFIC  
APPLICATION

## STANDARD RESPONSE

PUB.	SERIES	DEFLECTOR	K-FACTOR Imp.	SIN NUMBER	CONNECTION TYPE NPT in.   IGS Grooved	TEMPERATURE RATING F	APPROVALS	FINISHES AND CORROSIVE COATINGS	MAX. PRESSURE PSI	ESCUTCHEONS/ COVERPLATES NPT in. x ADJ in.	WRENCHES
41.51	FL-SR	Upright	2.8	V2861	½	135, 155, 175, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	NA	V56 Open End
	FL-SR	Upright	4.2	V4261	½	135, 155, 175, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	NA	V56 Open End
	FL-SR	Upright	5.6	V2703	½   IGS Grooved	135, 155, 175, 200, 286, 360	cULus, FM, LPCB, VdS, CCCf, CE	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	250	NA	V27 Open End, 3/16 Hex-Bit
	FL-SR	Upright	8.0	V3401	¾   IGS Grooved	135, 155, 175, 200, 286, 360	cULus, FM, LPCB, VdS, CE	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	NA	V34 Open End, 3/16 Hex-Bit
	FL-SR	Pendent and Recessed Pendent	2.8	V2851	½	135, 155, 175, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	½ x ½, ½ x ¾	V56-2 Recessed, V56 Open End
	FL-SR	Pendent and Recessed Pendent	4.2	V4251	½	135, 155, 175, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	½ x ½, ½ x ¾	V56-2 Recessed, V56 Open End
	FL-SR	Pendent and Recessed Pendent	5.6	V2707	½   IGS Grooved	135, 155, 175, 200, 286, 360	cULus, FM, LPCB, CCCf	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	250	½ x ½, ½ x ¾	V27-2 Recessed, V27 Open End, 3/16 Hex-Bit
	FL-SR	Pendent and Recessed Pendent	8.0	V3405	¾   IGS Grooved	135, 155, 175, 200, 286, 360	cULus, FM	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	¾ x ½, ¾ x ¾	V34-2 Recessed, V34 Open End, 3/16 Hex-Bit
41.52	FL-SR/SW	Horizontal Sidewall and Recessed Horizontal Sidewall	2.8	V2870	½	135, 155, 175, 200, 286, 360	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	½ x ½, ½ x ¾	V56-2 Recessed, V56 Open End
	FL-SR/SW	Horizontal Sidewall and Recessed Horizontal Sidewall	4.2	V4270	½	135, 155, 175, 200, 286, 360	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	½ x ½, ½ x ¾	V56-2 Recessed, V56 Open End
	FL-SR/SW	Horizontal Sidewall and Recessed Horizontal Sidewall	5.6	V2709	½   IGS Grooved	135, 155, 175, 200, 286, 360	cULus, FM, LPCB, CCCf, CE	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	250	½ x ½, ½ x ¾	V27-2 Recessed, V27 Open End, 3/16 Hex-Bit
	FL-SR/SW	Horizontal Sidewall and Recessed Horizontal Sidewall	8.0	V3409	¾   IGS Grooved	135, 155, 175, 200, 286, 360	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	¾ x ½, ¾ x ¾	V34-2 Recessed, V34 Open End, 3/16 Hex-Bit
41.53	FL-SR/C	Concealed Pendent	5.6	V5653	½	135, 155, 175, 200	cULus, FM	Plain Brass, Chrome, White, Bright White, Black, Custom	175	1	1" ADJ Concealed
	FL-SR/C	Concealed Pendent	5.6	V3807	½	135, 155, 175, 200	cULus	Plain Brass, Chrome, White, Bright White, Black, Custom	300	½	V38 Concealed
	FL-SR/C	Concealed Pendent	5.6	V3801	½	135, 155, 175, 200	cULus, LPCB, CCCf, CE	Plain Brass, Chrome, White, Bright White, Black, Custom	300	½	V38 Concealed
41.54	FL-SR/CNV	Conventional	5.6	V2725	½	135, 155, 175, 200, 286, 360	cULus, LPCB, VdS, CE	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	NA	V27 Open End
	FL-SR/CNV	Conventional	5.6	V2753	½	135, 155, 175, 200, 286, 360	cULus	Plain Brass, VC250	300	NA	V27 Open End
	FL-SR/CNV	Conventional	8.0	V8169	¾	135, 155, 175, 200, 286	cULus, FM, LPCB, CE	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	NA	V11 Open End
41.55	FL-SR/EUR	European Pendent	5.6	V2727	½	135, 155, 175, 200, 286, 360	cULus, LPCB, VdS, CE	Plain Brass, Chrome, White, Bright White, VC250	175	NA	V27 Recessed, V27 Open End
	FL-SR/EUR	European Pendent	8.0	V3423	¾	135, 155, 175, 200, 286, 360	LPCB, VdS, CE	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	NA	V34 Recessed, V34 Open End

NOTES: VC250: A Victaulic® proprietary coating that is UL listed and FM approved for corrosive environments. Clean Room Gasket Cover Plates available for all Concealed Pendent deflector sprinklers. Reference the Victaulic® price list or individual publications for more information.



# FIRELOCK AUTOMATIC SPRINKLERS

Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.



EXTENDED  
COVERAGE

RESIDENTIAL

STORAGE

DRY

SPECIFIC  
APPLICATION

## FLEXIBLE (QUICK RESPONSE)

PUB.	SERIES	DEFLECTOR	K-FACTOR Imp.	SIN NUMBER	CONNECTION TYPE NPT in.   IGS Grooved	TEMPERATURE RATING F	APPROVALS	FINISHES AND CORROSIVE COATINGS	MAX. PRESSURE PSI	ESCUTCHEONS/ COVERPLATES NPT in. x ADJ in.	WRENCHES
10.93	FL-SC/VS2	Pendent and Recessed Pendent	5.6	V3202	1   IGS Grooved	155, 200	cULus, FM	Chrome, White	175	¾ x ¾	V32 Open End Wrench
	FL-SC/VS2	Concealed Pendent	5.6	V3204 <sup>1</sup>	1   IGS Grooved	155, 200	cULus, FM <sup>1</sup>	Plain Brass	175	1/8	V32 Open End Wrench

## FLEXIBLE (STANDARD RESPONSE)

PUB.	SERIES	DEFLECTOR	K-FACTOR Imp.	SIN NUMBER	CONNECTION TYPE NPT in.   IGS Grooved	TEMPERATURE RATING F	APPROVALS	FINISHES AND CORROSIVE COATINGS	MAX. PRESSURE PSI	ESCUTCHEONS/ COVERPLATES NPT in. x ADJ in.	WRENCHES
10.93	FL-SC/VS2	Pendent and Recessed Pendent	5.6	V3201	1   IGS Grooved	155, 200	cULus, FM	Chrome, White	175	¾ x ¾	V32 Open End Wrench
	FL-SC/VS2	Concealed Pendent	5.6	V3203	1   IGS Grooved	155, 200	cULus	Plain Brass	175	1/8	V32 Open End Wrench

<sup>1</sup> V3204 is a Standard Response FM Sprinkler.

NOTES: VC250: A Victaulic® proprietary coating that is UL listed and FM approved for corrosive environments. Clean Room Gasket Cover Plates available for all Concealed Pendent deflector sprinklers. Reference the Victaulic® price list or individual publications for more information.

# FIRELOCK AUTOMATIC SPRINKLERS

Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.

STANDARD  
COVERAGE



EXTENDED  
COVERAGE

RESIDENTIAL

STORAGE

DRY

SPECIFIC  
APPLICATION

## LIGHT HAZARD

PUB.	SERIES	DEFLECTOR	K-FACTOR Imp.	SIN NUMBER	CONNECTION TYPE NPT in.   IGS Grooved	TEMPERATURE RATING F	APPROVALS	FINISHES AND CORROSIVE COATINGS	MAX. PRESSURE PSI	ESCUTCHEONS/ COVERPLATES NPT in. x ADJ in.	WRENCHES
42.01	FL-ECLH	Pendent and Recessed Pendent	5.6	V5614	½	135, 155, 175, 200	cULus	Plain Brass, Chrome, White, Bright White, Black, Custom	175	½ x ½, ½ x ¾	V56-2 Recessed, V56 Open End
	FL-ECLH	Pendent and Recessed Pendent	8.0	V3428	¾	135, 155, 175, 200	cULus	Plain Brass, Chrome, White, Bright White, VC250, Custom	175	¾ x ½, ¾ x ¾	V34 Recessed, V34 Open End
	FL-ECLH	Pendent and Recessed Pendent	11.2	V3412	¾	135, 155, 175, 200	cULus, FM	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	¾ x ¾ (cULus), ¾ x ½ (FM)	V34 Recessed, V34 Open End
	FL-ECLH	Pendent and Recessed Pendent	14.0	V3414	¾	135, 155, 175, 200	cULus, FM	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	¾ x ¾	V34 Recessed, V34 Open End
42.02	FL-ECLH/SW	Horizontal Sidewall and Recessed Horizontal Sidewall	5.6	V2758	½	135, 155, 175, 200	cULus, FM	Plain Brass, Chrome, White, Bright White, VC250, Custom	175	½ x ½ (cULus/FM), ½ x ¾ (cULus)	V27 Recessed, V27 Open End
	FL-ECLH/SW	Horizontal Sidewall and Recessed Horizontal Sidewall	8.0	V3416	¾	135, 155, 175, 200	cULus, FM	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	¾ x ½ (cULus/FM), ¾ x ¾ (cULus)	V34 Recessed, V34 Open End
42.03	FL-ECLH/SWDC	Domed Concealed Horizontal Sidewall	5.6	V5613	½	135, 155, 175	cULus	Plain Brass, Chrome, White, Bright White, Black, Custom	175	½	V56-2 Recessed
	FL-ECLH/SWDC	Domed Concealed Horizontal Sidewall	8.0	V8113	¾	135, 155, 175	cULus	Plain Brass, Chrome, White, Bright White, Black, Custom	175	½	V11-2 Recessed
	FL-ECLH/SWDC	Domed Concealed Horizontal Sidewall	8.0	V8114	¾	135, 155, 175	cULus	Plain Brass, Chrome, White, Bright White, Black, Custom	175	½	V11-2 Recessed
42.04	FL-ECLH/C	Concealed Pendent	5.6	V5603	½	135, 155, 175	cULus	Plain Brass, Chrome, White, Bright White, Black, Custom	175	1	V49/V56 1" ADJ Concealed
	FL-ECLH/C	Concealed Pendent	8.0	V3102	¾	135	cULus	Plain Brass, Chrome, White, Bright White, Black, Custom	175	5/8	V33 Concealed
	FL-ECLH/C	Concealed Pendent	11.2	V1106	¾	135, 155, 175, 200	cULus	Plain Brass, Chrome, White, Bright White, Black, Custom	175	1	V11 Concealed

## ORDINARY HAZARD

PUB.	SERIES	DEFLECTOR	K-FACTOR Imp.	SIN NUMBER	CONNECTION TYPE NPT in.   IGS Grooved	TEMPERATURE RATING F	APPROVALS	FINISHES AND CORROSIVE COATINGS	MAX. PRESSURE PSI	ESCUTCHEONS/ COVERPLATES NPT in. x ADJ in.	WRENCHES
42.51	FL-ECOH	Upright	11.2	V1121	¾	135, 155, 175, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	NA	V11 Recessed, V11 Open End
	FL-ECOH	Pendent and Recessed Pendent	11.2	V1113	¾	135, 155, 175, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	¾ x ½, ¾ x ¾	V11 Recessed, V11 Open End,
	FL-ECOH	Upright	14.0	V3425	¾   IGS Grooved	155, 175, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	NA	V34 Recessed, V34 Open End, 3/16 Hex-Bit
	FL-ECOH	Pendent and Recessed Pendent	14.0	V3421	¾   IGS Grooved	155, 175, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	¾ x ½, ¾ x ¾	V34 Recessed, V34 Open End, 3/16 Hex-Bit

NOTES: VC250: A Victaulic® proprietary coating that is UL listed and FM approved for corrosive environments. Clean Room Gasket Cover Plates available for all Concealed Pendent deflector sprinklers. Reference the Victaulic® price list or individual publications for more information.



# FIRELOCK AUTOMATIC SPRINKLERS

Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.



STANDARD  
COVERAGE

EXTENDED  
COVERAGE

RESIDENTIAL

STORAGE

DRY

SPECIFIC  
APPLICATION

## RESIDENTIAL

PUB.	SERIES	DEFLECTOR	K-FACTOR Imp.	SIN NUMBER	CONNECTION TYPE NPT in.   IGS Grooved	TEMPERATURE RATING F	APPROVALS	FINISHES AND CORROSIVE COATINGS	MAX. PRESSURE PSI	ESCUTCHEONS/ COVERPLATES NPT in. x ADJ in.	WRENCHES
43.01	FL-RES	Pendent and Recessed Pendent	3.0	V3010	½	155, 175, 200	cULus	Plain Brass, Chrome, White, Bright White, Black, Custom	175	½ x ½	V56 Recessed, V56 Open End
	FL-RES	Pendent and Recessed Pendent	4.9	V2740	½	155, 175	cULus	Plain Brass, Chrome, White, Bright White, VC250, Custom	175	12' x 12' – 18' x 18' spacing: ½ x ½, ½ x ¾ 20' x 20' spacing: ½ x ½	V27 Recessed, V27 Open End
	FL-RES	Pendent and Recessed Pendent	5.6	V5610	½	155	cULus	Plain Brass, Chrome, White, Bright White, Black, Custom	175	½ x ½	V56 Recessed, V56 Open End
	FL-RES	Pendent and Recessed Pendent	6.9	V3426	¾	155, 175	cULus	Plain Brass, Chrome, White, Bright White, VC250, Custom	175	¾ x ½, ¾ x ¾	V34 Recessed, V34 Open End
43.02	FL-RES/SW	Horizontal Sidewall and Recessed Horizontal Sidewall	4.2	V2738	½	155, 175	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	½ x ½, ½ x ¾	V27 Recessed, V27 Open End
	FL-RES/SW	Horizontal Sidewall and Recessed Horizontal Sidewall	4.4	V4431	½	155, 175	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	½ x ½, ½ x ¾	V56 Recessed, V56 Open End
	FL-RES/SW	Horizontal Sidewall and Recessed Horizontal Sidewall	5.6	V2744	½	155, 175	cULus	Plain Brass, Chrome, White, Bright White, VC250, Custom	175	½ x ½, ½ x ¾	V27 Recessed, V27 Open End
43.03	FL-RES/C	Concealed Pendent	4.9	V4906	½	155	cULus	Plain Brass, Chrome, White, Bright White, Black, Custom	175	1	V49/V56 1" ADJ Concealed
	FL-RES/C	Concealed Pendent	5.6	V3806	½	155	cULus	Plain Brass, Chrome, White, Bright White, Black, Custom	175	¼	V38 Concealed
43.04	FL-RES/DC	Domed Concealed	4.9	V2742	½	155	cULus	Chrome, White, Bright White, Black, Custom	175	7/16	V27 Concealed

NOTES: VC250: A Victaulic® proprietary coating that is UL listed and FM approved for corrosive environments. Clean Room Gasket Cover Plates available for all Concealed Pendent deflector sprinklers. Reference the Victaulic® price list or individual publications for more information.

# FIRELOCK AUTOMATIC SPRINKLERS

Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.



STANDARD  
COVERAGE

EXTENDED  
COVERAGE

RESIDENTIAL

STORAGE

DRY

SPECIFIC  
APPLICATION

## CONTROL MODE/DENSITY AREA CMDA

PUB.	SERIES	DEFLECTOR	K-FACTOR Imp.	SIN NUMBER	CONNECTION TYPE NPT in.   IGS Grooved	TEMPERATURE RATING F	APPROVALS	FINISHES AND CORROSIVE COATINGS	MAX. PRESSURE PSI	ESCUTCHEONS/ COVERPLATES NPT in. x ADJ in.	WRENCHES
44.01	FL-QR/ST	Upright	11.2	V3404	¾   IGS Grooved	135, 155, 175, 200, 286	cULus, FM	Plain Brass, Chrome, White, Bright White, VC250	175	NA	V34 Recessed, V34 Open End, 3/16 Hex-Bit
	FL-QR/ST	Pendent and Recessed Pendent	11.2	V3408	¾   IGS Grooved	135, 155, 175, 200, 286	cULus, FM	Plain Brass, Chrome, White, Bright White, VC250	175	¾ x ½ (cULus/FM), ¾ x ¾ (cULus)	V34 Recessed, V34 Open End, 3/16 Hex-Bit
44.51	FL-SR/ST	Upright	11.2	V3403	¾   IGS Grooved	135, 155, 175, 200, 286	cULus, FM	Plain Brass, Chrome, White, Bright White, VC250	175	NA	V34 Recessed, V34 Open End, 3/16 Hex-Bit
	FL-SR/ST	Pendent and Recessed Pendent	11.2	V3407	¾   IGS Grooved	135, 155, 175, 200, 286	cULus, FM	Plain Brass, Chrome, White, Bright White, VC250	175	¾ x ½ (cULus/FM), ¾ x ¾ (cULus)	V34 Recessed, V34 Open End, 3/16 Hex-Bit

## CONTROL MODE/SPECIFIC APPLICATION CMSA

PUB.	SERIES	DEFLECTOR	K-FACTOR Imp.	SIN NUMBER	CONNECTION TYPE NPT in.   IGS Grooved	TEMPERATURE RATING F	APPROVALS	FINISHES AND CORROSIVE COATINGS	MAX. PRESSURE PSI	ESCUTCHEONS/ COVERPLATES NPT in. x ADJ in.	WRENCHES
44.61	FL-SR/ST/ CMSA	CMSA Pendent	25.2	V4601	1   IGS Grooved	162, 212, 286	cULus, FM	Plain Brass	175	NA	V46 Open End, 3/16 Hex-Bit
44.62	FL-SR/ST/ CMSA	CMSA Upright	25.2	V4603	1   IGS Grooved	162, 212, 286	FM	Plain Brass	175	NA	V46 Open End, 3/16 Hex-Bit

NOTES: VC250: A Victaulic® proprietary coating that is UL listed and FM approved for corrosive environments. Clean Room Gasket Cover Plates available for all Concealed Pendent deflector sprinklers. Reference the Victaulic® price list or individual publications for more information.

# FIRELOCK AUTOMATIC SPRINKLERS

Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.

STANDARD  
COVERAGE

EXTENDED  
COVERAGE

RESIDENTIAL



STORAGE

DRY

SPECIFIC  
APPLICATION

## ESFR

PUB.	SERIES	DEFLECTOR	K-FACTOR Imp.	SIN NUMBER	CONNECTION TYPE NPT in.   IGS Grooved	TEMPERATURE RATING F	APPROVALS	FINISHES AND CORROSIVE COATINGS	MAX. PRESSURE PSI	ESCUTCHEONS/ COVERPLATES NPT in. x ADJ in.	WRENCHES
<a href="#">44.11</a>	FL-QR/ST/ ESFR	ESFR Pendent	16.8	V4702	¾   IGS Grooved	155, 200	cULus, FM	Plain Brass	175	NA	V47 Open End, 3/16 Hex-Bit
<a href="#">44.12</a>	FL-QR/ST/ ESFR	ESFR Pendent	22.4	V4806	1   IGS Grooved	165, 212	cULus	Plain Brass	175	NA	V46 Open End, 3/16 Hex-Bit
	FL-QR/ST/ ESFR	ESFR Pendent	22.4	V4808	1   IGS Grooved	165, 212	FM	Plain Brass	175	NA	V46 Open End, 3/16 Hex-Bit
<a href="#">44.13</a>	FL-QR/ST/ ESFR	ESFR Pendent	25.2	V4802	1   IGS Grooved	155, 200	cULus	Plain Brass	175	NA	V46 Open End, 3/16 Hex-Bit
	FL-QR/ST/ ESFR	ESFR Pendent	25.2	V4804	1   IGS Grooved	165, 212	cULus, FM	Plain Brass	175	NA	V46 Open End, 3/16 Hex-Bit

NOTES: VC250: A Victaulic® proprietary coating that is UL listed and FM approved for corrosive environments. Clean Room Gasket Cover Plates available for all Concealed Pendent deflector sprinklers. Reference the Victaulic® price list or individual publications for more information.

# FIRELOCK AUTOMATIC SPRINKLERS

Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.



STANDARD  
COVERAGE

EXTENDED  
COVERAGE

RESIDENTIAL

STORAGE

DRY

SPECIFIC  
APPLICATION

INTERMEDIATE

PUB.	SERIES	DEFLECTOR	K-FACTOR Imp.	SIN NUMBER	CONNECTION TYPE NPT in.   IGS Grooved	TEMPERATURE RATING F	APPROVALS	FINISHES AND CORROSIVE COATINGS	MAX. PRESSURE PSI	ESCUTCHEONS/ COVERPLATES NPT in. x ADJ in.	WRENCHES
44.21	FL-QR/ST/INT	Upright with Shield	5.6	V2704	½   IGS Grooved	135, 155, 175, 200, 286	cULus	Plain Brass	175	NA	V27 Open End, 3/16 Hex-Bit
	FL-QR/ST/INT	Upright with Shield	8.0	V3402	¾   IGS Grooved	135, 155, 175, 200, 286	cULus	Plain Brass	175	NA	V34 Open End, 3/16 Hex-Bit
	FL-QR/ST/INT	Upright with Shield	11.2	V3430	¾   IGS Grooved	135, 155, 175, 200, 286	cULus, FM	Plain Brass	175	NA	V34 Open End, 3/16 Hex-Bit
	FL-QR/ST/INT	Upright	5.6	V2704	½   IGS Grooved	135, 155, 175, 200, 286	cULus, FM, LPCB, VdS, CCCf, CE	Plain Brass	250	NA	V27 Open End, 3/16 Hex-Bit
	FL-QR/ST/INT	Upright	8.0	V3402	¾   IGS Grooved	135, 155, 175, 200, 286	cULus, FM, LPCB, VdS, CCCf, CE	Plain Brass	175	NA	V34 Open End, 3/16 Hex-Bit
	FL-QR/ST/INT	Upright	11.2	V3404	¾   IGS Grooved	135, 155, 175, 200, 286	cULus, FM	Plain Brass	175	NA	V34 Recessed, V34 Open End, 3/16 Hex-Bit
	FL-QR/ST/INT	Pendent	5.6	V2708	½   IGS Grooved	135, 155, 175, 200, 286	cULus, FM, CCCf	Plain Brass	250	NA	V27-2 Recessed, V27 Open End, 3/16 Hex-Bit
	FL-QR/ST/INT	Pendent	8.0	V3406	¾   IGS Grooved	135, 155, 175, 200, 286	cULus, FM, CCCf	Plain Brass	175	NA	V34-2 Recessed, V34 Open End, 3/16 Hex-Bit
44.71	FL-SR/ST/INT	Upright with Shield	5.6	V2703	½   IGS Grooved	135, 155, 175, 200, 286	cULus	Plain Brass	175	NA	V27 Open End, 3/16 Hex-Bit
	FL-SR/ST/INT	Upright with Shield	8.0	V3401	¾   IGS Grooved	135, 155, 175, 200, 286	cULus	Plain Brass	175	NA	V34 Open End, 3/16 Hex-Bit
	FL-SR/ST/INT	Upright with Shield	11.2	V3429	¾   IGS Grooved	135, 155, 175, 200, 286	cULus, FM	Plain Brass	175	NA	V34 Open End, 3/16 Hex-Bit
	FL-SR/ST/INT	Upright	5.6	V2703	½   IGS Grooved	135, 155, 175, 200, 286	cULus, FM, LPCB, VdS, CCCf, CE	Plain Brass	250	NA	V27 Open End, 3/16 Hex-Bit
	FL-SR/ST/INT	Upright	8.0	V3401	¾   IGS Grooved	135, 155, 175, 200, 286	cULus, FM, LPCB, VdS, CE	Plain Brass	175	NA	V34 Open End, 3/16 Hex-Bit
	FL-SR/ST/INT	Upright	11.2	V3403	¾   IGS Grooved	135, 155, 175, 200, 286	cULus, FM	Plain Brass	175	NA	V34 Recessed, V34 Open End, 3/16 Hex-Bit
	FL-SR/ST/INT	Pendent	5.6	V2707	½   IGS Grooved	135, 155, 175, 200, 286, 360	cULus, FM, LPCB, CCCf	Plain Brass	250	NA	V27-2 Recessed, V27 Open End, 3/16 Hex-Bit
	FL-SR/ST/INT	Pendent	8.0	V3405	¾   IGS Grooved	135, 155, 175, 200, 286, 360	cULus, FM	Plain Brass	175	NA	V34-2 Recessed, V34 Open End, 3/16 Hex-Bit
	FL-SR/ST/INT	Pendent	11.2	V3407	¾   IGS Grooved	135, 155, 175, 200, 286	cULus, FM	Plain Brass	175	NA	V34 Open End, 3/16 Hex-Bit

NOTES: VC250: A Victaulic® proprietary coating that is UL listed and FM approved for corrosive environments. Clean Room Gasket Cover Plates available for all Concealed Pendent deflector sprinklers. Reference the Victaulic® price list or individual publications for more information.

# FIRELOCK AUTOMATIC SPRINKLERS

Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.

STANDARD  
COVERAGE

EXTENDED  
COVERAGE

RESIDENTIAL

STORAGE



SPECIFIC  
APPLICATION

## QUICK RESPONSE

PUB.	SERIES	DEFLECTOR	K-FACTOR Imp.	SIN NUMBER	CONNECTION TYPE NPT in.   IGS Grooved	TEMPERATURE RATING F	APPROVALS	FINISHES AND CORROSIVE COATINGS	MAX. PRESSURE PSI	ESCUTCHEONS/ COVERPLATES NPT in. x ADJ in.	WRENCHES
45.01	FL-QR/DRY	Upright	5.6	V3602	1   IGS Grooved	135, 155, 200, 286	cULus, FM, CCC	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	NA	V36 Open End, 3/16 Hex-Bit
	FL-QR/DRY	Upright	8.0	V3604	1   IGS Grooved	135, 155, 200, 286	cULus, FM	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	NA	V36 Open End, 3/16 Hex-Bit
	FL-QR/DRY	Pendent and Recessed Pendent	5.6	V3614	1   IGS Grooved	135, 155, 200, 286	cULus, FM, CCC, CE	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	See Publication	V36 Recessed, V36 Open End, 3/16 Hex-Bit
	FL-QR/DRY	Pendent and Recessed Pendent	8.0	V3616	1   IGS Grooved	135, 155, 200, 286	cULus, FM, CCC, CE	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	See Publication	V36 Recessed, V36 Open End, 3/16 Hex-Bit
45.02	FL-QR/DRY/SW	Horizontal Sidewall and Recessed Horizontal Sidewall	5.6	V3610	1   IGS Grooved	135, 155, 200, 286	cULus, FM	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	See Publication	V36 Recessed, V36 Open End, 3/16 Hex-Bit
	FL-QR/DRY/SW	Horizontal Sidewall and Recessed Horizontal Sidewall	8.0	V3612	1   IGS Grooved	135, 155, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	See Publication	V36 Recessed, V36 Open End, 3/16 Hex-Bit
45.03	FL-QR/DRY/C	Concealed Pendent	5.6	V3302	1   IGS Grooved	135, 155, 200	cULus	Plain Brass, Chrome, White, Bright White, Black, Custom	175	1/2	V33 Concealed, 3/16 Hex-Bit
	FL-QR/DRY/C	Concealed Pendent	8.0	V3304	1   IGS Grooved	135, 155, 200	cULus	Plain Brass, Chrome, White, Bright White, Black, Custom	175	1/2	V33 Concealed, 3/16 Hex-Bit
	FL-QR/DRY/C	Concealed Pendent	5.6	V5634	1   IGS Grooved	135, 155, 175, 200	cULus, FM	Plain Brass, Chrome, White, Bright White, Black, Custom	175	1	V56/V81 RC Dry, V11 C ECLH
	FL-QR/DRY/C	Concealed Pendent	8.0	V8134	1   IGS Grooved	135, 155, 175, 200	cULus	Plain Brass, Chrome, White, Bright White, Black, Custom	175	1	V56/V81 RC Dry, V11 C ECLH
45.04	FL-QR/DRY/ST	Pendent and Recessed Pendent	11.2	V4002	1   IGS Grooved	135, 155, 175, 200, 286	cULus	Chrome, White, Bright White, VC250	175	See Publication	V36 Recessed, V36 Open End
45.05	FL-QR/DRY/VSW	Vertical Sidewall	5.6	V5643	1   IGS Grooved	155, 175, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	See Publication	V56/V81 RC Dry, V11 C ECLH
	FL-QR/DRY/VSW	Vertical Sidewall	8.0	V8143	1   IGS Grooved	155, 175, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	See Publication	V56/V81 RC Dry, V11 C ECLH

1 Dry type sprinklers are available in a variety of configurations (Flush Mount, Sleeve and Skirt, Plain Barrel, Intermediate, Extended, Recessed). Please refer to the individual product publication for specific details.  
 NOTES: VC250: A Victaulic® proprietary coating that is UL listed and FM approved for corrosive environments. Clean Room Gasket Cover Plates available for all Concealed Pendent deflector sprinklers. Reference the Victaulic® price list or individual publications for more information.

# FIRELOCK AUTOMATIC SPRINKLERS

Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.

STANDARD  
COVERAGE

EXTENDED  
COVERAGE

RESIDENTIAL

STORAGE



SPECIFIC  
APPLICATION

## STANDARD RESPONSE

PUB.	SERIES	DEFLECTOR	K-FACTOR Imp.	SIN NUMBER	CONNECTION TYPE NPT in.   IGS Grooved	TEMPERATURE RATING F	APPROVALS	FINISHES AND CORROSIVE COATINGS	MAX. PRESSURE PSI	ESCUTCHEONS/ COVERPLATES NPT in. x ADJ in.	WRENCHES
45.51	FL-SR/DRY	Upright	5.6	V3601	1   IGS Grooved	135, 155, 200, 286	cULus, FM, CCC	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	NA	V36 Open End, 3/16 Hex-Bit
	FL-SR/DRY	Upright	8.0	V3603	1   IGS Grooved	135, 155, 200, 286	cULus, FM	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	NA	V36 Open End, 3/16 Hex-Bit
	FL-SR/DRY	Pendent and Recessed Pendent	5.6	V3613	1   IGS Grooved	135, 155, 200, 286	cULus, FM, CCC, CE	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	See Publication	V36 Recessed, V36 Open End, 3/16 Hex-Bit
	FL-SR/DRY	Pendent and Recessed Pendent	8.0	V3615	1   IGS Grooved	135, 155, 200, 286	cULus, FM, CCC, CE	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	See Publication	V36 Recessed, V36 Open End, 3/16 Hex-Bit
45.52	FL-SR/DRY/SW	Horizontal Sidewall and Recessed Horizontal Sidewall	5.6	V3609	1   IGS Grooved	135, 155, 200, 286	cULus, FM	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	See Publication	V36 Recessed, V36 Open End, 3/16 Hex-Bit
	FL-SR/DRY/SW	Horizontal Sidewall and Recessed Horizontal Sidewall	8.0	V3611	1   IGS Grooved	135, 155, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	See Publication	V36 Recessed, V36 Open End, 3/16 Hex-Bit
45.53	FL-SR/DRY/C	Concealed Pendent	5.6	V3301	1   IGS Grooved	135, 155, 200	cULus	Plain Brass, Chrome, White, Bright White, Black, Custom	175	1/2	V33 Concealed, 3/16 Hex-Bit
	FL-SR/DRY/C	Concealed Pendent	8.0	V3303	1   IGS Grooved	135, 155, 200	cULus	Plain Brass, Chrome, White, Bright White, Black, Custom	175	1/2	V33 Concealed, 3/16 Hex-Bit
	FL-SR/DRY/C	Concealed Pendent	5.6	V5689	1   IGS Grooved	135, 155, 175, 200	cULus, FM	Plain Brass, Chrome, White, Bright White, Black, Custom	175	1	V56/V81 RC Dry, V11 C ECLH
	FL-SR/DRY/C	Concealed Pendent	8.0	V8189	1   IGS Grooved	135, 155, 175, 200	cULus	Plain Brass, Chrome, White, Bright White, Black, Custom	175	1	V56/V81 RC Dry, V11 C ECLH
45.54	FL-SR/DRY/ST	Pendent and Recessed Pendent	11.2	V4001	1   IGS Grooved	135, 155, 175, 200, 286	cULus	Chrome, White, Bright White, VC250	175	See Publication	V36 Recessed, V36 Open End
45.55	FL-SR/DRY/VSW	Vertical Sidewall	5.6	V5687	1   IGS Grooved	135, 155, 175, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	See Publication	V56/V81 RC Dry, V11 C ECLH
	FL-SR/DRY/VSW	Vertical Sidewall	8.0	V8187	1   IGS Grooved	135, 155, 175, 200, 286	cULus	Plain Brass, Chrome, White, Bright White, Black, VC250, Custom	175	See Publication	V56/V81 RC Dry, V11 C ECLH

1 Dry type sprinklers are available in a variety of configurations (Flush Mount, Sleeve and Skirt, Plain Barrel, Intermediate, Extended, Recessed). Please refer to the individual product publication for specific details.  
 NOTES: VC250: A Victaulic® proprietary coating that is UL listed and FM approved for corrosive environments. Clean Room Gasket Cover Plates available for all Concealed Pendent deflector sprinklers. Reference the Victaulic® price list or individual publications for more information.

# FIRELOCK AUTOMATIC SPRINKLERS

Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.

STANDARD  
COVERAGE

EXTENDED  
COVERAGE

RESIDENTIAL

STORAGE



SPECIFIC  
APPLICATION

## ESFR

PUB.	SERIES	DEFLECTOR	K-FACTOR Imp.	SIN NUMBER	CONNECTION TYPE NPT in.   IGS Grooved	TEMPERATURE RATING F	APPROVALS	FINISHES AND CORROSIVE COATINGS	MAX. PRESSURE PSI	ESCUTCHEONS/ COVERPLATES NPT in. x ADJ in.	WRENCHES
<a href="#">45.11</a>	FL-QR/DRY/ ESFR	Pendent	16.8	V4102	1	165, 212	cULus, FM	Plain Brass	175	Clamshell	3/16 Hex-Bit (V9)

<sup>1</sup> Dry type sprinklers are available in a variety of configurations (Flush Mount, Sleeve and Skirt, Plain Barrel, Intermediate, Extended, Recessed). Please refer to the individual product publication for specific details.  
 NOTES: VC250: A Victaulic<sup>®</sup> proprietary coating that is UL listed and FM approved for corrosive environments. Clean Room Gasket Cover Plates available for all Concealed Pendent deflector sprinklers. Reference the Victaulic<sup>®</sup> price list or individual publications for more information.

# FIRELOCK AUTOMATIC SPRINKLERS

Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.

STANDARD  
COVERAGE

EXTENDED  
COVERAGE

RESIDENTIAL

STORAGE



SPECIFIC  
APPLICATION

## FLEXIBLE DRY SPRINKLER (QUICK RESPONSE)

PUB.	SERIES	DEFLECTOR	K-FACTOR Imp.	SIN NUMBER	CONNECTION TYPE NPT in.   IGS Grooved	TEMPERATURE RATING F	APPROVALS	FINISHES AND CORROSIVE COATINGS	MAX. PRESSURE PSI	ESCUTCHEONS/ COVERPLATES NPT in. x ADJ in.	WRENCHES
10.91	FL-DRY/VS1	Pendent and Recessed Pendent	5.6	V3506	1	135, 155, 175, 200, 286	cULus	White, VC250	175	See Publication	Any Commercially Available Wrench
	FL-DRY/VS1	Horizontal Sidewall and Recessed Horizontal Sidewall	5.6	V3510	1	135, 155, 175, 200, 286	cULus	White, VC250	175	See Publication	Any Commercially Available Wrench
	FL-DRY/VS1	Concealed Pendent	5.6	V3518	1	135, 155, 175, 200	cULus	White, VC250	175	See Publication	Any Commercially Available Wrench

## FLEXIBLE DRY SPRINKLER (STANDARD RESPONSE)

PUB.	SERIES	DEFLECTOR	K-FACTOR Imp.	SIN NUMBER	CONNECTION TYPE NPT in.   IGS Grooved	TEMPERATURE RATING F	APPROVALS	FINISHES AND CORROSIVE COATINGS	MAX. PRESSURE PSI	ESCUTCHEONS/ COVERPLATES NPT in. x ADJ in.	WRENCHES
10.91	FL-DRY/VS1	Pendent and Recessed Pendent	5.6	V3505	1	135, 155, 175, 200, 286	cULus	White, VC250	175	See Publication	Any Commercially Available Wrench
	FL-DRY/VS1	Horizontal Sidewall and Recessed Horizontal Sidewall	5.6	V3509	1	135, 155, 175, 200, 286	cULus	White, VC250	175	See Publication	Any Commercially Available Wrench
	FL-DRY/VS1	Concealed Pendent	5.6	V3517	1	135, 155, 175, 200	cULus	White, VC250	175	See Publication	Any Commercially Available Wrench

1 Dry type sprinklers are available in a variety of configurations (Flush Mount, Sleeve and Skirt, Plain Barrel, Intermediate, Extended, Recessed). Please refer to the individual product publication for specific details.  
 NOTES: VC250: A Victaulic® proprietary coating that is UL listed and FM approved for corrosive environments. Clean Room Gasket Cover Plates available for all Concealed Pendent deflector sprinklers. Reference the Victaulic® price list or individual publications for more information.

# FIRELOCK AUTOMATIC SPRINKLERS

Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.



STANDARD  
COVERAGE

EXTENDED  
COVERAGE

RESIDENTIAL

STORAGE

DRY

## INTERSTITIAL SPACE

PUB.	SERIES	DEFLECTOR	K-FACTOR Imp.	SIN NUMBER	CONNECTION TYPE NPT in.   IGS Grooved	TEMPERATURE RATING F	APPROVALS	FINISHES AND CORROSIVE COATINGS	MAX. PRESSURE PSI	ESCUTCHEONS/ COVERPLATES NPT in. x ADJ in.	WRENCHES
46.01	FL-SA/IC	Upright	5.6	V5608	½	175, 200	cULus	Plain Brass	175	NA	V56 Open End

## ATTIC

PUB.	SERIES	DEFLECTOR	K-FACTOR Imp.	SIN NUMBER	CONNECTION TYPE NPT in.   IGS Grooved	TEMPERATURE RATING F	APPROVALS	FINISHES AND CORROSIVE COATINGS	MAX. PRESSURE PSI	ESCUTCHEONS/ COVERPLATES NPT in. x ADJ in.	WRENCHES
46.02	FL-SA/DS	Upright	5.6	V5621	½	200	cULus	Plain Brass	175	NA	V56 Open End
	FL-SA/RE	Upright	5.6	V5620	½	200	cULus	Plain Brass	175	NA	V56 Open End
46.03	FL-SA/GAP	Upright	5.6	V5623	½	200	cULus	Plain Brass	175	NA	V56 Open End
	FL-SA/BB	Upright (4:12 to less than 7:12)	8.0	V8122	¾	200	cULus	Plain Brass	175	NA	V11 Open End
	FL-SA/BB	Upright (7:12 to less than 10:12)	8.0	V8123	¾	200	cULus	Plain Brass	175	NA	V11 Open End
	FL-SA/BB	Upright (10:12 to 12:12)	8.0	V8124	¾	200	cULus	Plain Brass	175	NA	V11 Open End
	FL-SA/BB	Upright (4:12 to less than 7:12)	5.6	V5618	½	200	cULus	Plain Brass	175	NA	V11 Open End
	FL-SA/BB	Upright (7:12 to less than 10:12)	5.6	V5619	½	200	cULus	Plain Brass	175	NA	V11 Open End
	FL-SA/BB	Upright (10:12 to 12:12)	5.6	V5625	½	200	cULus	Plain Brass	175	NA	V11 Open End

NOTES: VC250: A Victaulic® proprietary coating that is UL listed and FM approved for corrosive environments. Clean Room Gasket Cover Plates available for all Concealed Pendent deflector sprinklers. Reference the Victaulic® price list or individual publications for more information.

# FIRELOCK AUTOMATIC SPRINKLERS

Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.

STANDARD  
COVERAGE

EXTENDED  
COVERAGE

RESIDENTIAL

STORAGE

DRY



## WINDOW AND NOZZLES

PUB.	SERIES	DEFLECTOR	K-FACTOR Imp.	SIN NUMBER	CONNECTION TYPE NPT in.   IGS Grooved	TEMPERATURE RATING F	APPROVALS	FINISHES AND CORROSIVE COATINGS	MAX. PRESSURE PSI	ESCUTCHEONS/ COVERPLATES NPT in. x ADJ in.	WRENCHES
46.04	FL-SA/WS	Vertical Sidewall	5.6	V2752	½	155, 200	cULus	Plain Brass, Chrome Plated, White Polyester Painted, Custom Polyester Painted, VC-250	175	½ x ¾	V27 Open End V27-2 Concealed/ Recessed
	FL-SA/WS	Concealed Pendent	5.6	V5648	½	155, 200	cULus	Plain Brass, Chrome Plated, White Polyester Painted, Custom Polyester Painted, VC-250	175	1	V49/V56 1" ADJ Concealed
47.01	FL-SA/NZ	Window Nozzle	1.4	V1001	½	Open	cULus	Plain Brass, Chrome	175	NA	Any Commercially Available Wrench
	FL-SA/NZ	Window Nozzle	2.0	V1003	½	Open	cULus	Plain Brass, Chrome	175	NA	Any Commercially Available Wrench
	FL-SA/NZ	Window Nozzle	2.8	V1005	½	Open	cULus	Plain Brass, Chrome	175	NA	Any Commercially Available Wrench
	FL-SA/NZ	Window Nozzle	4.2	V1007	½	Open	cULus	Plain Brass, Chrome	175	NA	Any Commercially Available Wrench
	FL-SA/NZ	Window Nozzle	5.6	V1009	½	Open	cULus	Plain Brass, Chrome	175	NA	Any Commercially Available Wrench
	FL-SA/NZ	Window Nozzle	8.0	V1011	¾	Open	cULus	Plain Brass, Chrome	175	NA	Any Commercially Available Wrench
	FL-SA/NZ	Window Nozzle	11.4	V1013	¾	Open	cULus	Plain Brass, Chrome	175	NA	Any Commercially Available Wrench
47.02	FL-SA/NZ	Foam Nozzle	2.8	V2601	½	Open	cULus	Plain Brass	175	NA	Any Commercially Available Wrench
	FL-SA/NZ	Foam Nozzle	5.6	V2603	½	Open	cULus	Plain Brass	175	NA	Any Commercially Available Wrench
47.03	FL-SA/NZ	Directional Nozzle	1.2	V1201 – V1208	½	Open	cULus, FM	Plain Brass, VC250	175	NA	Any Commercially Available Wrench
	FL-SA/NZ	Directional Nozzle	1.8	V1211 – V1218	½	Open	cULus, FM	Plain Brass, VC250	175	NA	Any Commercially Available Wrench
	FL-SA/NZ	Directional Nozzle	2.3	V1221 – V1228	½	Open	cULus, FM	Plain Brass, VC250	175	NA	Any Commercially Available Wrench
	FL-SA/NZ	Directional Nozzle	3.2	V1231 – V1238	½	Open	cULus, FM	Plain Brass, VC250	175	NA	Any Commercially Available Wrench
	FL-SA/NZ	Directional Nozzle	4.1	V1241 – V1248	½	Open	cULus, FM	Plain Brass, VC250	175	NA	Any Commercially Available Wrench
	FL-SA/NZ	Directional Nozzle	4.9	V1251 – V1258	½	Open	cULus, FM	Plain Brass, VC250	175	NA	Any Commercially Available Wrench
	FL-SA/NZ	Directional Nozzle	5.6	V1261 – V1268	½	Open	cULus, FM	Plain Brass, VC250	175	NA	Any Commercially Available Wrench
	FL-SA/NZ	Directional Nozzle	7.2	V1271 – V1278	½	Open	cULus, FM	Plain Brass, VC250	175	NA	Any Commercially Available Wrench

NOTES: VC250: A Victaulic® proprietary coating that is UL listed and FM approved for corrosive environments. Clean Room Gasket Cover Plates available for all Concealed Pendent deflector sprinklers. Reference the Victaulic® price list or individual publications for more information.



PITCH-SPRINKLERS 16955 REV N 01/2026  
Victaulic and all other Victaulic marks are the trademarks or registered trademarks of Victaulic Company, and/or its affiliated entities, in the U.S. and/or other countries. All other trademarks listed herein are the property of their respective holders, in the U.S. and/or other countries. The terms "Patented" or "Patent Pending" refer to design or utility patents or patent applications for articles and/or methods of use in the United States and/or other countries.