



**FireLock™ Style 912
Anboringsklammer**

Størrelse tommer mm			Hullstørrelse Minimum	Hullstørrelse Maks	Moment N•m	Smøring
1 33.7	x	1/2 15	24	25.4	27.1	Nei
1 1/4 42.4	x	1/2 15	24	25.4	27.1	Nei
1 1/2 48.3	x	1/2 15	24	25.4	27.1	Nei



FireLock™ Style 922 Anboringsklammer				
Størrelse tommer DN	Hullstrørelse Minimum	Hullstrørelse Maks	Moment N•m	Smøring
1 1/4 32	30	32	27.1	Nei
x				
1/2 15				
3/4 20				
	30	32	27.1	Nei
1 1/2 40				
x				
1/2 15				
	30	32	27.1	Nei
2 50				
x				
1/2 15				
	30	32	27.1	Nei
2 1/2 65				
x				
1/2 15				
	30	32	27.1	Nei
2 1/2 65				
x				
1/2 15				
	30	32	27.1	Nei
2 1/2 65				
x				
1/2 15				
	30	32	27.1	Nei
2 1/2 65				
x				
1/2 15				



FireLock™ Style 922 IGS						
Anboringsklammer						
Størrelse tommer DN		Hullstrørelse Minimum	Hullstrørelse Maks	Moment N•m	Smøring	
1 1/4 32	x	1 25	30	32	47.5	Nei
1 1/2 40	x	1 25	30	32	47.5	Nei
2 50	x	1 25	30	32	47.5	Nei
2 1/2 65	x	1 25	30	32	47.5	Nei



Style 920/920N Anbøringsklammer				
Grentilkobling tommer DN	Hullstrørelse Minimum	Hullstrørelse Maks	Moment N•m	Smøring
1/2" 15	38	41	68	Ja
3/4" 20	38	41	68	Ja
1" 25	38	41	68	Ja
1 1/4" 32	44	48	68	Ja



Style 920/920N Anboringsklammer				
Grentilkobling tommer DN	Hullstrørel se Minimum	Hullstrørel se Maks	Moment N·m	Smøring
1 1/2" 40	51	54	68	Ja
Bortsett fra Style 920N 2 x 1 1/2" 50 x 40	44	48		
Bortsett for Style 920N 10, 12, 14 x 1 1/2" 250, 300, 350 x 40	70	73		
2" 50	64	67	68	Ja
Bortsett fra Style 920 og 920N 8 x 2" 200 x 50	70	73		
2 1/2" 65	70	73	68	Ja
3" 80	89	92	68	Ja
4" 100	114	118	68	Ja