

Julie

IP65 LED Luminaire



With a tough exterior, Julie is the optimal choice for industrial and commercial applications

- High quality, low energy lighting in wet and dusty environments
- High quality opal diffuser for uniform lighting
- Ideal for replacement and refurbishment projects
- CONNECT version with quick connector for easy installation available
- 2200lm (19 W), 3200lm (28 W), 4200lm (38 W), 6300lm (55 W), 8600lm (76 W) up to 116lm/W
- Colour temperature 4000 K
- Versions with presence sensor and corridor function



IP65:
Dust tight and water resistant



Save up to 60% energy compared to T8 fluorescent



IK08 rated impact resistance



Lengths of 632, 1232, 1532 and 1800 mm



3h emergency version available



Presence sensor with corridor function

Ideal for ...



Workshops



Underpasses



Storage facilities

Specification

- Class I electrical
- IK08
- IP65
- ENEC certified driver
- Ambient operating temperature: -20 to +40°C (E3: 0 to +25°C)

Installation/Mounting


Suitable for surface mounting. 4x10 mm stainless steel self-tapping screws (not included) can be applied to prevent unauthorised opening of the luminaire.

Material/Finish

Canopy: Polycarbonate
Diffuser: Opal polycarbonate (UV stabilised)
Bracket: Stainless steel

JULIE 600 LED IP65 2200
JULIE 1200 LED IP65 3200
JULIE 1200 LED IP65 4200
JULIE 1500 LED IP65 4200
JULIE 1500 LED IP65 6300
JULIE 1800 LED IP65 8600

L	W	H
632	103	78
1232	85	71
1232	103	78
1532	85	71
1532	103	78
1800	103	78




Light distribution

115 lm/W



Julie LED 6300lm
cd/klm ULOR: 8 %
DLOR: 92 %
LOR: 100 %




Presence sensor with corridor function

Julie's microwave sensor option with corridor function will ensure that you never walk in the dark. The settings are fully adjustable, with the additional benefit of a daylight sensor.

Sensor range

at 100% sensitivity



Controllability

Sensitivity	10 %, 50 %, 75 %, 100 %
Time	5 s, 30 s, 60 s, 5 min, 10 min, 20 min, 30 min
lux	2 lux, 10 lux, 50 lux, disable
Stand-by time	0 sec, 10 sec, 1 min, 10 min, 30 min, 60 min, endless
Dimming Level	10 %, 20 %, 30 %, 50 %

Ordering guide

Description	SAP Code
JULIE 600 LED IP65 2200 840	96628548
JULIE 1200 LED IP65 3200 840	96631255
JULIE 1200 LED IP65 4200 840	96665577
JULIE 1500 LED IP65 4200 840	96628396
JULIE 1500 LED IP65 6300 840	96665580
JULIE 1800 LED IP65 8600 840	96631143
JULIE 1200 LED IP65 4200 840 CONNECT	96665578
JULIE 1500 LED IP65 6300 840 CONNECT	96665581
JULIE 1800 LED IP65 8600 840 CONNECT	96631300
JULIE 1200 LED IP65 4200 840 COR MWS	96630234
JULIE 1500 LED IP65 4200 840 COR MWS	96630235
JULIE 1500 LED IP65 6300 840 COR MWS	96630236
JULIE 1200 LED IP65 4200 840 TW	96630239
JULIE 1500 LED IP65 4200 840 TW	96630240
JULIE 1500 LED IP65 6300 840 TW	96630241
Emergency versions	
JULIE 1200 LED IP65 3200 840 E3	96631404
JULIE 1200 LED IP65 4200 840 E3	96665579
JULIE 1500 LED IP65 4200 840 E3	96628397
JULIE 1500 LED IP65 6300 840 E3	96665582
JULIE 1800 LED IP65 8600 840 E3	96631144
JULIE 1200 LED IP65 4200 840 COR MWS E3	96631093
JULIE 1500 LED IP65 4200 840 COR MWS E3	96631094
JULIE 1500 LED IP65 6300 840 COR MWS E3	96631095
Spare parts	
JULIE LED Spare Mount Kit	96628409
JULIE LED CONNECT Spare Mount Kit	96628410
JULIE LED Suspension Kit	96631301

MWS: microwave presence sensor COR: corridor function TW: through-wired
CONNECT: with quick connector

Light source information

- Lifetime 50 000 hours (@L70, Ta 25 °C)
- 2200lm (19W), 3200lm (28W), 4200lm (38W), 6300lm (55W), 8600lm (76W) up to 116lm/W
- Colour temperature 4000K
- CRI80
- MacAdam (initial): 4



Five year guarantee